

Impact Nutrunners

Reversible



MP2260 Series

- High power to weight ratio
- Speed of a screwdriver, power of an impact
- Ideal for soft joint applications
- 4 built-in speed control regulator positions for varying torque output
- Smooth and efficient impact mechanism creates no torque reaction
- Compact clutch design
- 100% ball bearing design
- Reversible
- Detachable belt clip (MP2264, MP2265)



MP2264



MP2265



MP2266

FASTENING

Model Number	Drive	Torque Range		Free Speed	Blows Per Minute	Bolt Capacity		Weight		Air Consumption
	In.	Ft.Lbs.	Nm	RPM		in.	mm	lbs.	kg	CFM
Pistol										
MP2264	1/4 QC	10-100	13.5-135	10,000	1700	1/2"	10	2.2	1	20
MP2265	3/8 SQ*	10-100	13.5-135	10,000	1700	1/2"	10	2.2	1	20
Inline										
MP2266	1/4 QC	10-100	13.5-135	9,500	1700	1/2"	10	2.2	1	20

General:

Air Inlet 1/4" NPT
 Use 1/4" (6.4 mm) I.D. hose
 All tools performance rated @ 90psi (620 kPa) air pressure.
 *Pin retainer

Standard Equipment:

Owners Manual
 Parts Sheet

Optional Accessories:

60538 Master Guard oil (4 oz.)
 60539 Master Guard oil (1 qt.)
 22034 Hose Line Oiler
 70497000 Flow Regulator
 88007045 Trigger Assembly Kit, MP2264, MP2265



It is the user's responsibility to refer and comply with ANSI B7.1

WARNING: Face & eye protection must be worn while operating power tools, per ANSI B186.1. Cutting tool maximum speed rating must be equal or exceed speed of air tool @ 90 psi (620 kPa). Follow cutting tool manufacturer's mounting & operating instructions.